

CLOTH TAPE



Product Code	Pricing Unit	Colour	Size	Pack Quantity	Pallet Quantity
TGB	EACH	Black	48mm x 50m	24	480
TGB2	EACH	Black	72mm x 50m	16	320
TGB3	EACH	Black	96mm x 50m	12	240
TGS	EACH	Silver	48mm x 50m	24	480
TGS2	EACH	Silver	72mm x 50m	16	320
TGS3	EACH	Silver	96mm x 50m	12	240
TGW	EACH	White	48mm x 50m	24	480

Product Description:

An aggressive, high tack, easy tear, waterproof tape ideal for joining textured protection materials plus many other heavy-duty applications. It is invaluable for use around the home, workshop, and garden or on construction sites. Commonly known as gaffer tape.

The tape comes in black, white and silver and three different width rolls.

Benefits:

- Ideal for a wide range of applications
- Durable and strong
- Water resistant
- Highly adhesive

Limitations:

- May leave residue. Use *Proguard Low Tack PVC Tape* for sensitive surfaces.
- Not 100% waterproof – if submerged under water this tape may come loose.

Application:

Temperature: between 0°C and + 35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C. Apply the tape by hand or with a *Proguard Tape Applicator*.

Performance Data:

Adhesive	Coated with Vacuum hotmelt adhesive(synthetic Rubber)
Weave	35mesh
Carrier	Woven polyester and cotton-coated, blended with LDPE
Total Thickness	0.17±0.01mm
Adhesion to Steel	>47.5oz/inch
Tensile Strength	>25N/CM
Rolling ball tack	> 10 (Ball no.)
Elongation	10-20%
Service temperature range	-15°C -> + 70°C