

PROGUARD

WE'VE GOT IT **COVERED**

6 MONTH WINDOW PROTECTION FILM



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PFW116M	EACH	CLEAR	600mm x 100m	50 micron	9	90

Product Description:

Proguard 6 Month Window Protection Film is perfect for reducing clean up time at the end of a building, painting, or DIY project. It is a 100% waterproof, high-quality self-adhesive film designed specifically for the protection of windows, glazed panels, and window frames. Windows are highly susceptible to scratches, plaster, and paint splashes especially during external rendering, paint spraying and decorating projects. Self-adhesive protective film for windows can help you avoid the additional cost of extensive cleaning or window replacement.

The lightweight self-adhesive film rolls are forward wound (adhesive side is innerside) which makes the rolls perfect for application with our Proguard Window Film Applicator or by hand. As the adhesive is on the innerside it is not exposed to dirt. The low tack adhesive backing sticks to most hard surfaces without any tape required and will stay securely in place once applied. After use, it can be peeled away without leaving any residue which can be a problem with poor quality films. Unlike some alternative products Proguard Window Protector roll has Anti-UV properties to ensure that direct sunlight does not cause the adhesive to transfer onto the windows.

Benefits:

- Can be left in-situ for up to 6 months without leaving residue.
- Self-adhesive for easy application – no taping required.
- Clear – allows light into the room.
- Lightweight, easy-to-handle rolls.
- High tear & puncture resistance.
- 100% waterproof.
- Easy to cut with a knife.
- Personalised logo and branding printing available (Minimum quantities applicable)

Limitations:

- Product may become slippery when wet. Mop up any spills immediately or replace where necessary.
- This product is for application to windows and other glass surfaces. DO NOT use on carpets. Use Proguard Carpet Protection film.
- Adhesion will be reduced on dusty surfaces. Vacuuming prior to use is recommended.
- Always check Proguard Window Film is stuck firmly to windows before commencing work.
- Do not use heated windows whilst product is in situ.
- On delicate surfaces, we advise that you test on a small area first.
- It is the users' responsibility to determine suitability for use. If in doubt, contact technical services for advice.
- Not fire-retardant.

Application:

Ensure surfaces to which Proguard Window Protection Film is to be applied are clean, sound, dust free and dry. Remove outer packaging from roll. Unwind approx. 600mm of material and stick this to the top of the window. Pull the roll down towards the floor. Smooth out with hands as it unwinds.

Performance Data:

Temperature Resistance	60°C 160hours
Tensile Strength	≥50 N/mm
Adhesive	Pressure Sensitive Acrylic
Adhesive Strength	370 g/50mm
UV resistance	Up to 6 months
Backing	PE(LDPE and LLDPE) film