

### FLAME RETARDANT SCAFFOLD SHEETING



Product Code	Pricing Unit	Colour	Dimensions	Weight	Pack Quantity	Pallet Quantity
PSDSF1	Each	White	2m x 45m	180gsm	1	20

Proguard flame retardant scaffold sheets are manufactured from high quality polyethylene material. The puncture and tear resistant sheets are ideal for protecting scaffold structures, especially during bad weather.

The sheets come with eyelets for easy installation using cable ties. The sheets are versatile and will fit most scaffold structures. Comes with the added benefit of being flame-retardant.

#### Benefits:

- Flame retardant (non-certified)
- Ideal for protecting scaffold structures.
- Versatile
- Eyelets allow for quick and easy installation.

#### Limitations:

- Must be secured with cable ties or bungee toggle ties.

#### Application:

Unroll the scaffold sheeting and cover the scaffolding. Secure with our *Proguard Cable Ties* or *Bungee Toggle Ties*.

#### Performance Data:

Material	HDPE scrim and LDPE lamination
Color	White colour with White reinforced webbing band
Weave	3X3/sq. inch
Denier	2400
Weight per m <sup>2</sup>	180g/m <sup>2</sup> (+/-5%)
Test method	ASTM-1682
Tensile strength (Warp)	31.4kg
Tensile strength (Weft)	20kg
Elongation (Warp)	27.10%
Elongation (Weft)	22.70%
Eyelet per roll	With pre-punched eyelet holes on the 7cm-wide reinforced band. Interval between each eyelet is 10cm. Total 3 bands across the roll width.
Use	External use only