

PROGUARD

WE'VE GOT IT

COVERED

DOUBLE SIDED DUO TAPE



Product Code	Pricing Unit	Colour	Size	Pack Quantity	Pallet Quantity
TSD1	Each	Clear	50mm x 50m	24	480

Product Description:

Proguard duo tape is a double-sided tape with high tack one side & low tack the other side. It is often used when fixing protection materials to finished surfaces. For example Proguard Protection Board could be fixed to a wall using Duo tape - the low tack would adhere to the wall and the high tack to the protection board.

Benefits:

- Ideal for fixing temporary protection materials to finished surfaces
- One side low-tack and the other side high-tack
- Highly adhesive
- Available in a variety of roll sizes

Limitations:

- Not 100% waterproof – if submerged under water this tape may come loose.

Application:

Temperature: between +5°C to +25°C Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. Apply the tape by hand removing the backing paper as you go. The low tack side should be adhered to the finished surface and the high tack side should be adhered to the temporary protection material.

Performance Data:

Thickness Adhesive & Carrier	0.050mm
Release Liner Thickness	0.075mm
180° Peel Adhesion (Open Side)	400 N/m
(Closed Side)	150 N/m
Polyester Loop Tack (Open Side)	800 N/m
(Closed Side)	100 N/m
Liner Release	10 N/m
Tensile Strength	4600 N/m
Elongation at Break	12%
Service Temperature	-20°C to +120°C
Sheer Adhesion (1Kg @ 23°C)	>2 Hours