

PROGUARD

WE'VE GOT IT

COVERED

FLAME RETARDANT PREMIUM CARPET PROTECTION FILM



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PFCF11E	EACH	White	600mm x 100m	65 micron	9	90

Product Description:

Proguard Flame Retardant Premium Carpet Protection Film is perfect for protecting carpets from spillages and debris during building, painting, DIY projects, house moves, parties and other events to help reduce clean up time. The adhesive backing adheres to most carpets and carpet tiles and ensures that the film stays securely in place, making it safer to use than traditional dust sheets and polythene. After use, it can be peeled away without leaving any residue.

The rolls are forward wound meaning the adhesive side is on the inside which makes the rolls perfect for application with our Proguard Film Applicator or by hand. As the adhesive is on the inside it is not exposed to dirt.

This carpet film has the added benefit of being flame retardant and anti-slip due to its embossed finish.

Benefits:

- Self-adhesive for easy application – no taping required
- Lightweight, easy-to-handle rolls
- High tear & puncture resistance
- Anti-slip
- Flame-retardant
- 100% waterproof
- Easy to cut with a knife
- Personalised logo and branding printing available (Minimum quantities applicable)
- Film is white in colour
- Available in a range of widths and lengths

Limitations:

- Although this product has a high-level of slip resistance it may become slippery when wet. Mop up any spills immediately or replace where necessary.
- This product is for application to carpets, DO NOT use on hard surfaces. Use Proguard Hard Surface Protection film.
- Obviously, adhesion will be reduced on dusty surfaces. Vacuuming prior to use is recommended.
- Proguard Carpet Protection Film should be removed after a maximum of 40 days.
- Always check Proguard Carpet Protection Film is stuck firmly to carpets before commencing work.
- Do not use underfloor heating whilst product is in situ.
- On delicate carpets, we advise that you test on a small area first.
- It is the users' responsibility to determine suitability for use. If in doubt contact technical services for advice.

Application:

Ensure surfaces to which Proguard Carpet Film is to be applied are clean sound, dust free and dry. Remove outer packaging from roll. Place roll on the floor facing the direction it is to be applied and unwind approx. 600mm of material. Ensure the roll is stuck by smoothing out by either hand or foot. Simply pull the roll towards you ensuring it goes in a straight line. Smooth out with hands or feet as it unwinds. A very effective way of laying Proguard Carpet Film is to push the roll along with a soft broom/brush using the brush to smooth out and remove air bubbles as it unwinds.

Performance Data:

Temperature Resistance	60°C 160hours
Tensile Strength	≥45 N/mm
Adhesive	Pressure Sensitive Acrylic Solvent
Adhesive Strength	1300-1500 g/50mm
Backing	PE(LDPE and LLDPE) film
Slip Characteristics (when dry)	64PTV - Low risk