

FLAME RETARDANT PVC TAPE



Product Code	Pricing Unit	Colour	Size	Pack Quantity	Pallet Quantity
TFR1	Each	Grey	50mm x 33m	36	540

Product Description:

Our low-tack fire retardant PVC tape is ideal for joining protection materials such as the Proguard Protection Board. It is especially good for joining protection materials to sensitive surfaces as the low tack adhesive won't leave residue. Surfaces must be clean and free from dust for this product to work effectively. Fire resistant to BS EN 60454.

Benefits:

- Ideal for protection of sensitive surfaces
- Removes without leaving residue
- Water-resistant
- Flame resistant to BS EN 60454

Limitations:

- If you require high tack adhesion use *Proguard Cloth Tape*.
- Not 100% waterproof – if submerged under water this tape may come loose.

Application:

Temperature: between 0°C and +60°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C. Apply the tape by hand.

Performance Data:

Adhesive	Natural Rubber
Total Thickness	0.13±0.01mm
Adhesion to Steel	≥3N/In
Tensile Strength	≥40N/In
Rolling ball tack	≥5
Elongation	≥150%