

## FOIL TAPE



Product Code	Pricing Unit	Colour	Size	Pack Quantity	Pallet Quantity
TAF1	Each	Silver	48mm x 45m	24	480
TAF2	Each	Silver	72mm x 45m	16	320
TAF3	Each	Silver	96mm x 45m	12	240

### Product Description:

This aluminium, self-adhesive foil tape is widely used in the construction industry for pipe lagging, duct sealing, heating and ventilation. It is fire-rated to the recognised 'Class O' certification.

### Benefits:

- Suitable for joining pipe lagging, heating and ventilation repairs
- Fire resistant – Class O
- Self-adhesive
- Available in a variety of roll sizes
- Suitable for use in cold weather

### Application:

Temperature: between 10°C and + 40°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C.

### Performance Data:

Adhesive	Cold weather solvent acrylic adhesive
Carrier	Easy-release silicone release paper
Total Thickness	70micron
Backing Thickness	30micron
Adhesion to Steel	15N/25mm
Tensile Strength	45N/25mm
Rolling ball tack	5cm
Service temperature range	-35°C -> + 120°C