

### HARD SURFACE PROTECTION FILM



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PFM31	EACH	Blue	600mm x 25m	50 micron	16	160
PFM21	EACH	Blue	600mm x 50m	50 micron	12	120
PFM11	EACH	Blue	600mm x 100m	50 micron	9	90

#### Product Description:

Proguard Hard Surface Protection Film is perfect for reducing clean up time at the end of a building, painting or DIY project. It is a 100% waterproof, high-quality self-adhesive film designed specifically for protecting hard surfaces such as vinyl, marble, tiles and cured timber floors. It is particularly popular with the decorating trade as it prevents damage to hard floors and surfaces from spillages and other debris. The low-tack adhesive backing ensures that the film stays securely in place, making it safer to use than traditional dust sheets and polythene.

The lightweight self-adhesive film rolls are forward wound (adhesive side is inner side) which makes the rolls perfect for application with our Proguard Film Applicator or by hand. As the adhesive is on the inner side near it is not exposed so as to collect dirt. The low tack adhesive backing sticks to most hard surfaces without any tape required and will stay securely in place once applied. After use, it can be peeled away without leaving any residue which can be a problem with poor quality films.

#### Benefits:

- Self-adhesive for easy application – no taping required.
- Lightweight, easy-to-handle rolls.
- High tear & puncture resistance.
- 100% waterproof.
- Easy to cut with a knife.
- Personalised logo and branding printing available (Minimum quantities applicable)
- Film is clear in colour.
- Available in a range of widths and lengths.

#### Limitations:

- Product may become slippery when wet. Mop up any spills immediately or replace where necessary.
- This product is for application to hard surfaces, DO NOT use on carpets. Use Proguard Carpet Protection film.
- Obviously, adhesion will be reduced on dusty surfaces. Vacuuming prior to use is recommended.
- Proguard Hard Surface Protection Film should be removed after a maximum of 40 days.
- Always check Proguard Hard Surface Film is stuck firmly to carpets before commencing work.
- Do not use underfloor heating whilst product is in situ.
- On delicate surfaces, we advise that you test on a small area first.
- It is the users' responsibility to determine suitability for use. If in doubt contact technical services for advice.
- Not flame-retardant.

#### Application:

Ensure surfaces to which Proguard Hard Surface Protection Film is to be applied are clean sound, dust free and dry. Remove outer packaging from roll. Place roll on the floor facing the direction it is to be applied and unwind approx. 600mm of material. Ensure the roll is stuck by smoothing out by either hand or foot. Simply pull the roll towards you ensuring it goes in a straight line. Smooth out with hands or feet as it unwinds. A very effective way of laying Proguard Hard Surface Protection Film is to push the roll along with a soft broom/brush using the brush to smooth out and remove air bubbles as it unwinds.

#### Performance Data:

Temperature Resistance	60°C 160hours
Tensile Strength	≥45 N/mm
Adhesive	Pressure Sensitive Acrylic Solvent
Adhesive Strength	370-430 g/50mm
Backing	PE(LDPE and LLDPE) film
Slip Characteristics (when dry)	64PTV - Low risk