

HAZARD WARNING TAPE



Product Code	Pricing Unit	Colour	Size	Pack Quantity	Pallet Quantity
THARW	Each	Red/White	50mm x 33m	24	480
THAYB	Each	Yellow/Black	50mm x 33m	24	480

Product Description:

A tough PVC tape with brightly coloured chevrons to provide a hazard warning. Our self-adhesive hazard tape can be used on concrete floors for creating walkways or cordoning off areas.

Benefits:

- Suitable for internal and external use
- Highly visible
- Moisture resistant

Limitations:

- Non fire retardant.
- Not 100% waterproof – if submerged under water this tape may come loose.

Application:

Temperature: between 0°C and + 35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23 °C. Apply the tape by hand or with a *Proguard Tape Applicator*.

Performance Data:

Adhesive	Natural Rubber
Carrier	Red/white or black /yellow PVC film
Total Thickness	0.15±0.05mm
Adhesion to Steel	≥3n/in
Tensile Strength	≥35N/in
Rolling ball tack	> 10(Ball no.)
Elongation	≥150%
Service temperature range	0°C -> + 80°C