

## REVERSE WOUND CARPET PROTECTION FILM



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PFCR31	EACH	Clear	600mm x 25m	50 micron	16	160
PFCR21	EACH	Clear	600mm x 50m	50 micron	12	120
PFCR11	EACH	Clear	600mm x 100m	50 micron	9	90

### Product Description:

Proguard Carpet Protection Film is perfect for protecting carpets from spillages and debris during building, painting, DIY projects, house moves, parties and other events to help reduce clean up time. The adhesive backing adheres to most carpets and carpet tiles and ensures that the film stays securely in place, making it safer to use than traditional dust sheets and polythene. After use, it can be peeled away without leaving any residue.

The lightweight self-adhesive film rolls are reverse wound (adhesive side is outermost) which makes the rolls easy to apply by simply 'kicking' out in front of you or with our Proguard Film Applicator. The adhesive backing sticks to most hard surfaces without any tape required and will stay securely in place once applied. After use, it can be peeled away without leaving any residue which can be a problem with poor quality films.

### Benefits:

- Self-adhesive for easy application – no taping required.
- Reverse wound – simply 'kick' out across the floor.
- Lightweight, easy-to-handle rolls.
- High tear & puncture resistance.
- 100% waterproof.
- Easy to cut with a knife.
- Personalised logo and branding printing available (Minimum quantities applicable)
- Film is clear in colour.
- Available in a range of widths and lengths.

### Limitations:

- Product may become slippery when wet. Mop up any spills immediately or replace where necessary.
- This product is for application to carpets, DO NOT use on hard surfaces. Use Proguard Hard Surface Protection film.
- Obviously, adhesion will be reduced on dusty surfaces. Vacuuming prior to use is recommended.
- Proguard Carpet Protection Film should be removed after a maximum of 40 days.
- Always check Proguard Carpet Protection Film is stuck firmly to carpets before commencing work.
- Do not use underfloor heating whilst product is in situ.
- On delicate carpets, we advise that you test on a small area first.
- It is the users' responsibility to determine suitability for use. If in doubt contact technical services for advice.

### Application:

Ensure surfaces to which Proguard Carpet Film is to be applied are clean sound, dust free and dry. Remove outer packaging from roll. Place roll on the floor facing the direction it is to be applied and unwind approx. 600mm of material. Ensure the roll is stuck by smoothing out by either hand or foot. Simply pull the roll towards you ensuring it goes in a straight line. Smooth out with hands or feet as it unwinds. A very effective way of laying Proguard Carpet Film is to push the roll along with a soft broom/brush using the brush to smooth out and remove air bubbles as it unwinds.

### Performance Data:

Temperature Resistance	60°C 160hours
Tensile Strength	≥45 N/mm
Adhesive	Pressure Sensitive Acrylic Solvent
Adhesive Strength	1300-1500 g/50mm
Backing	PE(LDPE and LLDPE) film
Slip Characteristics (when dry)	64PTV - Low risk